

AA 203 Recitation #1: Automatic Differentiation with JAX

Spencer M. Richards, Matt Foutter, Daniel Morton

April 5, 2024

1 JAX

JAX follows the *functional programming* paradigm. That is, JAX provides tools to transform a function into another function. Specifically, JAX can automatically compute the *derivative* of a function or composition of functions.

As an example, for $f(x) = \frac{1}{2}\|x\|_2^2$, JAX computes $\nabla f : \mathbb{R}^n \rightarrow \mathbb{R}^n$ where $\nabla f(x) = x$.

```
[ ]: import jax
import jax.numpy as jnp

def f(x):
    return jnp.sum(x**2)/2    # identical to numpy syntax

grad_f = jax.grad(f)        # compute the gradient function

x = jnp.array([0., 1., 2.]) # use JAX arrays!
print('x:          ', x)
print('f(x):       ', f(x))
print('grad_f(x):  ', grad_f(x))
```

WARNING:jax._src.lib.xla_bridge:No GPU/TPU found, falling back to CPU. (Set TF_CPP_MIN_LOG_LEVEL=0 and rerun for more info.)

```
x:          [0.  1.  2.]
f(x):       2.5
grad_f(x):  [0.  1.  2.]
```

2 Automatic Differentiation

Automatic Differentiation (AD, autodiff) uses pre-defined derivatives and the chain rule to compute derivatives of more complex functions.

Consider the function $f : \mathbb{R}^n \rightarrow \mathbb{R}^m$. The Jacobian of f evaluated at the point $x \in \mathbb{R}^n$ is the matrix

$$\partial f(x) = \begin{bmatrix} \frac{\partial f_1}{\partial x_1}(x) & \frac{\partial f_1}{\partial x_2}(x) & \cdots & \frac{\partial f_1}{\partial x_n}(x) \\ \frac{\partial f_2}{\partial x_1}(x) & \frac{\partial f_2}{\partial x_2}(x) & \cdots & \frac{\partial f_2}{\partial x_n}(x) \\ \vdots & \vdots & \ddots & \vdots \\ \frac{\partial f_m}{\partial x_1}(x) & \frac{\partial f_m}{\partial x_2}(x) & \cdots & \frac{\partial f_m}{\partial x_n}(x) \end{bmatrix} = \left[\frac{\partial f_i}{\partial x_j}(x) \right]_{i=1, j=1}^{m, n} \in \mathbb{R}^{m \times n}.$$

As for any matrix, the Jacobian $\partial f(x) : \mathbb{R}^n \rightarrow \mathbb{R}^m$ is a linear map $v \mapsto \partial f(x)v$ defined by the usual matrix-vector multiplication rules.

AD can be used to compute the *Jacobian-Vector Product (JVP)*

$$\begin{aligned} \partial f(x) : \mathbb{R}^n &\rightarrow \mathbb{R}^m \\ v &\mapsto \partial f(x)v \end{aligned}$$

and the *Vector-Jacobian Product (VJP)*

$$\begin{aligned} \partial f(x)^\top : \mathbb{R}^m &\rightarrow \mathbb{R}^n \\ w &\mapsto \partial f(x)^\top w \end{aligned}$$

The maps $v \mapsto \partial f(x)v$ and $w \mapsto \partial f(x)^\top w$ are also known as the *pushforward* and *pullback*, respectively, of f at x . The vector x is referred to as the primal, while the vectors v and w are termed *seeds* in AD literature.

Consider the function composition

$$h(x) = (f_N \circ f_{N-1} \circ \dots \circ f_1)(x) = f_N(f_{N-1}(\dots f_1(x) \dots)),$$

where each $f_k : \mathbb{R}^{d_k} \rightarrow \mathbb{R}^{d_{k+1}}$ is some differentiable map.

We can write this recursively as

$$y_0 = x \in \mathbb{R}^n, \quad \underbrace{y_{k+1} = f_{k+1}(y_k) \in \mathbb{R}^{d_{k+1}}}, \quad y_N = h(x) \in \mathbb{R}^{d_N}.$$

By the chain rule, we have

$$\partial h(x) = \partial f_N(y_{N-1}) \partial f_{N-1}(y_{N-2}) \dots \partial f_1(y_0).$$

This sequence of matrix multiplications that can get quickly get expensive for complicated functions!

It is more efficient and usually sufficient in practice to compute JVPs via the recursion

$$\begin{aligned} \partial h(x)v_0 &= \partial f_N(y_{N-1}) \partial f_{N-1}(y_{N-2}) \dots \partial f_1(y_0)v_0 \\ &= v_N, \\ v_k &= \underbrace{\partial f_k(y_{k-1})v_{k-1}} \end{aligned}$$

and VJPs via the recursion

$$\begin{aligned} \partial h(x)^\top w_0 &= \partial f_1(y_0)^\top \dots \partial f_{N-1}(y_{N-2})^\top \partial f_N(y_{N-1})^\top w_0 \\ &= w_N, \\ w_k &= \underbrace{\partial f_{N-k+1}(y_{N-k})^\top w_{k-1}} \end{aligned}$$

VJPs require more memory than JVPs, since $\{y_k\}_{k=1}^{N-1}$ must be computed and stored first (i.e., the *forward pass*) before recursing (i.e., the *backward pass*).

2.1 Example: VJP as a gradient

For a scalar function $f: \mathbb{R}^n \rightarrow \mathbb{R}$, the Jacobian at x is $\partial f(x) \in \mathbb{R}^{1 \times n}$, so

$$\nabla f(x) = \partial f(x)^\top \mathbf{1}.$$

E.g., if $f(x) = \frac{1}{2}\|x\|_2^2$, then $\nabla f(x) = x \cdot \mathbf{1}$.

```
[ ]: f = lambda x: jnp.sum(x**2)/2 # anonymous functions work as well
x = jnp.array([0., 1., 2.])
f_x, dfxT = jax.vjp(f, x) # compute forward pass and VJP function
dfxT_1 = dfxT(1.)

print('x: ', x)
print('f(x): ', f_x)
print('dfxT(1):', dfxT_1)
```

```
x: [0. 1. 2.]
f(x): 2.5
dfxT(1): (DeviceArray([0., 1., 2.], dtype=float32),)
```

2.2 Example: JVP as a directional derivative

The directional derivative of $f: \mathbb{R}^n \rightarrow \mathbb{R}$ at $x \in \mathbb{R}^n$ along $v \in \mathbb{R}^n$ is

$$\nabla f(x)^\top v = \partial f(x)v.$$

E.g., if $f(x) = \frac{1}{2}\|x\|_2^2$, then $\nabla f(x)^\top v = x^\top v$.

```
[ ]: f = lambda x: jnp.sum(x**2)/2
x = jnp.array([0., 1., 2.])
v = jnp.array([1., 1., 1.]) ←

# use tuples to separate inputs from seeds
f_x, dfx_v = jax.jvp(f, (x,), (v,))

print('x: ', x)
print('f(x): ', f_x)
print('dfx(v):', dfx_v)
```

$f(x)$ ←
 $\partial f(x)v$ ←

```
x: [0. 1. 2.]
f(x): 2.5
dfx(v): 3.0
```

2.3 Example: Multi-input, multi-output VJP

Let's try something more complicated:

$$f: \mathbb{R}^n \times \mathbb{R}^n \rightarrow \mathbb{R} \times \mathbb{R}$$

$$(x, y) \mapsto \left(\frac{1}{2} \|x\|_2^2 + \frac{1}{2} \|y\|_2^2, \sum_{i=1}^n x_i \right)$$

$f_1(x, y)$ $f_2(x, y)$

$$f = \begin{bmatrix} f_1 \\ f_2 \end{bmatrix}$$

```
[ ]: def f(x, y):
    f1 = jnp.sum(x**2)/2 + jnp.sum(y**2)/2
    f2 = jnp.sum(x)
    return f1, f2

x = jnp.array([0., 1., 2.])
y = jnp.array([0., 1., 2.])
f_xy, dfT = jax.vjp(f, x, y)

print('x,y:      ', x, y)
print('f(x,y):   ', f_xy)
print('dfT(1,1):', dfT((1., 1.))) # provide tuple as input
```

$\partial_x f(x, y) [1]$

$\partial_y f(x, y) [1]$

```
x,y:      [0. 1. 2.] [0. 1. 2.]
→ f(x,y): (DeviceArray(5., dtype=float32), DeviceArray(3., dtype=float32))
dfT(1,1): (DeviceArray([1., 2., 3.], dtype=float32), DeviceArray([0., 1., 2.], dtype=float32))
```

2.4 Example: VJP and JVP for a Matrix Input

We can generalize VJPs and JVPs to non-vector inputs as well:

$$f: \mathbb{R}^{n \times n} \rightarrow \mathbb{R}$$

$$X \mapsto a^T X b$$

```
[ ]: def f(X):
    a, b = jnp.array([0., 1., 2.]), jnp.array([0., 1., 2.])
    return a @ (X @ b)

X = jnp.ones((3, 3))
f_x = f(X)
w, V = jnp.array(1.), jnp.eye(3)
f_x, dfT = jax.vjp(f, X)
f_x, df_v = jax.jvp(f, (X,), (V,))

print('X:\n', X, '\n', 'f(X): ', f_x, '\n', sep='')
print('dfT(1):\n', dfT(w), '\n', 'df(I): ', df_v, sep='')
```

```
X:
[[1. 1. 1.]
 [1. 1. 1.]
```

```

[1. 1. 1.]
f(X): 9.0

dfT(1):
(DeviceArray([[0., 0., 0.],
              [0., 1., 2.],
              [0., 2., 4.]], dtype=float32),)
df(I): 5.0

```

3 Auto-Vectorizing Functions with `jax.vmap`

For some complicated function $f : \mathbb{R}^n \rightarrow \mathbb{R}^m$, we want to calculate $f(x)$ for *many* different values of x without looping.

This is known as *vectorizing* a function. JAX can do this automatically!

```

[ ]: f = lambda x: jnp.array([jnp.sum(x**2)/2, jnp.linalg.norm(x, jnp.inf)])
     f = jax.vmap(f) in axis = 0

     batch_size, n = 100, 3
     x = jnp.ones((batch_size, n)) # dummy values with desired shape

     print(x.shape)
     print(f(x).shape)

```

```

(100, 3) ←
(100, 2) ←

```

*for row in x:
Store f(row)*

3.1 Example: Batch Evaluation of a Neural Network

```

[ ]: def f(x, W, b):
     return W[1] @ jnp.tanh(W[0] @ x + b[0]) + b[1]
     → f = jax.vmap(f, in_axes=(0, None, None))
     → f = jax.vmap(f, in_axes=(0, None, None))

     n, m = 3, 5
     batch_size = 100
     hdim = 32

     W = (jnp.ones((hdim, n)), jnp.ones((m, hdim)))
     b = (jnp.ones(hdim), jnp.ones(m))
     x = jnp.ones((40, batch_size, n))

     print(x.shape)
     print(f(x, W, b).shape)

```

*x → 3D
batch → 2D*

*for batch in x:
→ for vec in batch:
Store f(vec, W, b)*

```

(40, 100, 3)
(40, 100, 5)

```

3.2 Example: Jacobian Matrix from JVPs and VJPs

Let $e_k^{(d)} \in \{0, 1\}^d$ denote the k^{th} coordinate vector in d dimensions.

For $f: \mathbb{R}^n \rightarrow \mathbb{R}^m$, we can compute the full Jacobian $\partial f(x) \in \mathbb{R}^{m \times n}$ with either n JVPs

$$\underline{\partial f(x)} = \partial f(x) I_n = \begin{bmatrix} \underbrace{\partial f(x) e_1^{(n)}} & \underbrace{\partial f(x) e_2^{(n)}} & \dots & \underbrace{\partial f(x) e_n^{(n)}} \end{bmatrix},$$

or m VJPs

$$\partial f(x)^\top = \partial f(x)^\top I_m = \begin{bmatrix} \underbrace{\partial f(x)^\top e_1^{(m)}} & \partial f(x)^\top e_2^{(m)} & \dots & \partial f(x)^\top e_m^{(m)} \end{bmatrix}.$$

$n \gg 1$

$x \in \mathbb{R}^n$

$f(x) = L(x)$

$f: \mathbb{R}^n \rightarrow \mathbb{R}$

$\partial f(x) \in \mathbb{R}^{1 \times n}$

This is what the source code for `jax.jacrev` and `jax.jacrev` does.

```
[ ]: f = lambda x: jnp.array([x[0], x[0]**2 + x[2]**2])
      f1(x)    f2(x)
def df(x, v):
    fx, dfx_v = jax.jvp(f, (x,), (v,))
    return dfx_v

def dfT(x, w):
    fx, dfxT = jax.vjp(f, x)
    return dfxT(w)[0] # need to index into tuple (value,)

n, m = 3, 2
x = jnp.ones(n)
Jx = jax.vmap(df, in_axes=(None, 0))(x, jnp.eye(n))
JxT = jax.vmap(dfT, in_axes=(None, 0))(x, jnp.eye(m))
print('Jacobian (forward AD):')
print(Jx)
print('\nJacobian (reverse AD):')
print(JxT)
```

Jacobian (forward AD):

```
[[1. 2.]
 [0. 0.]
 [0. 2.]]
```

Jacobian (reverse AD):

```
[[1. 0. 0.]
 [2. 0. 2.]]
```

3.3 Example: Linearizing Dynamics at Many Points


For $\dot{x} = f(x, u)$ with $x \in \mathbb{R}^n$ and $u \in \mathbb{R}^m$, recall the first-order Taylor approximation

$$f(x, u) \approx \underbrace{f(\bar{x}_k, \bar{u}_k)}_{=c_k} + \underbrace{\partial_x f(\bar{x}_k, \bar{u}_k)}_{=A_k} \underbrace{(x - \bar{x})}_{\Delta x_t} + \underbrace{\partial_u f(\bar{x}_k, \bar{u}_k)}_{=B_k} \underbrace{(u - \bar{u})}_{\Delta u_t}$$

←

We want $A_k \Delta x_t$, $B_k \Delta u_t$, and c_k for $\{(\bar{x}_k, \bar{u}_k)\}_{k=1}^K$ and $\{(\Delta x_t, \Delta u_t)\}_{t=1}^T$.

This scenario may correspond to evaluating Taylor approximations for T perturbations $(\Delta x_t, \Delta u_t)$ that we want to test at the K points (\bar{x}_k, \bar{u}_k) .



```
[ ]: # Inverted pendulum (with unit mass and unit length)
f = lambda x, u: jnp.array([x[1], 9.81*jnp.sin(x[0]) + u[0]])

def taylor(x_bar, u_bar, dx, du):
    f_x_bar_u_bar, A_dx = jax.jvp(lambda x: f(x, u_bar), (x_bar,), (dx,))
    B_du = jax.jvp(lambda u: f(x_bar, u), (u_bar,), (du,))
    return f_x_bar_u_bar, A_dx, B_du

print(type(taylor))

n, m = 2, 1
K, T = 5, 10
x_bar, u_bar = jnp.ones((K, n)), jnp.ones((K, m))
dx, du = jnp.ones((T, n)), jnp.ones((T, m))

taylor = jax.vmap(taylor, in_axes=(None, None, 0, 0))
print(type(taylor))


taylor = jax.vmap(taylor, in_axes=(0, 0, None, None))
print(type(taylor))

c, Ax, Bu = taylor(x_bar, u_bar, dx, du)
print(c.shape)
print(Ax.shape)
print(Bu.shape)
```

$$\frac{\partial f(\bar{x}_k, \bar{u}_k)}{\partial x} \Delta x_t = A_k \Delta x_t$$

1: $\mathcal{O}(K)$
2: $\mathcal{O}(T)$

```
<class 'function'>
<class 'function'>
<class 'function'>
(5, 10, 2)
(5, 10, 2)
(5, 10, 2)
```



If, instead, we have $K = 5$ trajectories $\{(\bar{x}_k, \bar{u}_k)\}_{k=1}^K$ and each trajectory \bar{x}_k has $T = 10$ timesteps $\{(\bar{x}_{k,t}, \bar{u}_{k,t})\}_{t=1}^T$, and similarly for $(\Delta x, \Delta u)$, then we can evaluate Taylor approximations for all these trajectories with two calls to vmap as below.

```
[ ]: # Inverted pendulum (with unit mass and unit length)
f = lambda x, u: jnp.array([x[1], 9.81*jnp.sin(x[0]) + u[0]])
def taylor(x_bar, u_bar, dx, du):
    f_x_bar_u_bar, A_dx = jax.jvp(lambda x: f(x, u_bar), (x_bar,), (dx,))
    f_x_bar_u_bar, B_du = jax.jvp(lambda u: f(x_bar, u), (u_bar,), (du,))
    return f_x_bar_u_bar, A_dx, B_du
```

```

n, m = 2, 1
K, T = 5, 10
x̄ = jnp.ones((K, T, n)) # note the different sizes
ū = jnp.ones((K, T, m))
Δx, Δu = jnp.ones((K, T, n)), jnp.ones((K, T, m))

# two successive calls to vmap:
# we linearize for the K trajectories that each have T timesteps
taylor = jax.vmap(taylor)
taylor = jax.vmap(taylor)

c, Ax, Bu = taylor(x̄, ū, Δx, Δu)
print(c.shape)
print(Ax.shape)
print(Bu.shape)

```

```

(5, 10, 2)
(5, 10, 2)
(5, 10, 2)

```

4 Other Features and Nuances of JAX

See the [JAX documentation](#) for more details.

4.1 Just-In-Time (JIT) Compilation

JAX can compile code to run fast on both CPUs and GPUs. The first call to a “jitted” function will compile and cache the function; subsequent calls are then much faster.

```

[ ]: def selu(x, alpha=1.67, lmbda=1.05):
      return lmbda * jnp.where(x > 0, x, alpha * jnp.exp(x) - alpha)

x = jnp.ones(int(1e7))
%timeit -r10 -n100 selu(x).block_until_ready()

selu_jit = jax.jit(selu)
%timeit -r10 -n100 selu_jit(x).block_until_ready()

```

```

42.5 ms ± 2.95 ms per loop (mean ± std. dev. of 10 runs, 100 loops each)
10.4 ms ± 426 μs per loop (mean ± std. dev. of 10 runs, 100 loops each)

```

4.2 In-Place Updates

JAX arrays are immutable. In keeping with the functional programming paradigm, updates to array values at indices are done via JAX functions.

```

[ ]: X = jnp.zeros((3,3))
      try:

```



```

X[0, :] = 1.
except Exception as e:
    print("Exception: {}".format(e))
print('\nX:\n', X, sep='')

Y = X.at[0, :].set(1.)
print('\nY:\n', Y, sep='')

```

Exception: '<class 'jaxlib.xla_extension.DeviceArray'>' object does not support item assignment. JAX arrays are immutable. Instead of ``x[idx] = y``, use ``x = x.at[idx].set(y)`` or another .at[] method:

https://jax.readthedocs.io/en/latest/_autosummary/jax.numpy.ndarray.at.html

```

X:
[[0. 0. 0.]
 [0. 0. 0.]
 [0. 0. 0.]]

```

```

Y:
[[1. 1. 1.]
 [0. 0. 0.]
 [0. 0. 0.]]

```

4.3 Pseudo-Random Number Generation (PRNG)

JAX does explicit PRNG; after initializing a PRNG state, it can be forked into new PRNG states for parallel stochastic generation.

This enables reproducible results; propagate the key and make new subkeys whenever new random numbers are needed.

```

[ ]: seed = 0
key = jax.random.PRNGKey(seed)
print(jax.random.normal(key, shape=(1,)))
print(jax.random.normal(key, shape=(1,))) # same value sampled!

print('\nkey', key)
key, *subkeys = jax.random.split(key, 3)
print('|-- SPLIT --> key      ', key)
print('      --> subkeys', subkeys[0],
      '--> normal', jax.random.normal(subkeys[0], shape=(1,)))
print('      ', subkeys[1],
      '--> normal', jax.random.normal(subkeys[1], shape=(1,)))

```

```

[-0.20584226]
[-0.20584226]

```

```

key [0 0]
|-- SPLIT --> key      [2467461003  428148500]

```

```
--> subkeys [3186719485 3840466878] --> normal [0.5781488]
           [2562233961 1946702221] --> normal [0.8535516]
```